(11)Publication number:

2000-353820

(43) Date of publication of application: 19.12.2000

(51)Int.CI.

H01L 33/00 H01S 5/183 H01S 5/323

(21)Application number: 11-166352

(71)Applicant : SHOWA DENKO KK

(22)Date of filing:

14.06.1999 (72)Ii

(72)Inventor: UDAGAWA TAKASHI

Zanventor.


NABEKURA WATARU

TAKEUCHI RYOICHI

## (54) AlGaInP LIGHT EMITTING ELEMENT WITH WINDOW LAYER (57) Abstract:

PROBLEM TO BE SOLVED: To acquire an AlGaInP light emitting element of high brightness by providing a specified p-type clad layer, a light emitting layer and an n-type clad layer in a GaAs single crystalline substrate and providing a window layer consisting of zinc oxide thereon.

SOLUTION: P-type clad layers 104, 106 consisting of  $(AI\alpha Ga1-\alpha)$  xIn1-xP  $(0\leq \alpha\leq 1,0< x<1)$ , a light emitting layer 105, an n-type clad layer and a window layer 107 of a polycrystalline zinc oxide are formed on a GaAs single crystalline substrate 101. In the process, the composition ratio (1-X) of indium of an AlGaInP layer is made 0.5, thereby obtaining good lattice-match to a GaAs substrate 101. It is desirable that zinc oxide is hexagonal wurtzite type crystal, a polycrystalline zinc oxide film is preferably orientated C-axially and the resistivity is made  $1\times 103$   $\Omega$ .cm or less. Although zinc oxide crystal shows n-type conduction in its so-called undoped state wherein impurities are not added intentionally, an n-type zinc oxide window layer 107 of lower resistivity can be formed by doping a group III element.



## **LEGAL STATUS**

[Date of request for examination]

[Date of sending the examiner's decision of rejection]

[Kind of final disposal of application other than the examiner's decision of rejection or application converted registration]

[Date of final disposal for application]

[Patent number]

[Date of registration]
[Number of appeal against examiner's decision of rejection]
[Date of requesting appeal against examiner's decision of rejection]
[Date of extinction of right]

Copyright (C); 1998,2003 Japan Patent Office